

IPS WELD-ON		MATERIAL SAFETY DATA SHEET		Date Revised: MAR 2005 Supersedes: MAY 2004		
Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. IPS Corporation urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on this sheet.						
SECTION I						
MANUFACTURER'S NAME IPS Corporation ADDRESS 17109 S. Main St., P.O. Box 379, Gardena, CA. 90248			Transportation Emergencies: CHEMTREC: (800) 424-9300 Medical Emergencies: 3 E COMPANY (24 Hour No.) (800) 451-8346 Business: (310) 898-3300			
CHEMICAL NAME and FAMILY Acrylic cement Mixture of Acrylic Resin and Organic Solvents			TRADE NAME: WELD-ON 16 for Acrylic FORMULA: Proprietary			
SECTION II - HAZARDOUS INGREDIENTS						
One of the ingredients listed below is listed as a carcinogen (‡) by IARC and NTP						
	CAS#	APPROX %	ACGIH-TLV	ACGIH-STEL	OSHA-PEL	OSHA-STEL
Synthetic Acrylic Resin	NON/HAZ	5 - 20	N/A		N/A	
Methylene Chloride (‡)	75-09-2	30 - 60*	50 PPM		25 PPM	125 PPM
Methyl Acetate	79-20-9	0 - 35*	200 PPM	250 PPM	200 PPM	
Methyl Ethyl Ketone	78-93-3	0 - 40*	200 PPM	300 PPM	200 PPM	300 PPM
Methyl Methacrylate Monomer	80-62-6	0 - 5	100 PPM		100 PPM	
All of the constituents of Weld-On adhesive products are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that list.						
*Title III Section 313 Supplier Notification: This product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.						
PROPOSITION 65 NOTICE						
This product contains chemicals known to the state of California to cause cancer.						
This material is an aspiration hazard and defats the skin. The ingredients are toxic by inhalation and ingestion and may be absorbed through the skin. Exposure by these routes may cause central nervous system depression, liver and kidney damage and may sensitize the heart muscle. Methylene Chloride may interfere with the oxygen carrying capacity of the blood. Methylene Chloride is a possible human cancer hazard based on test results with laboratory animals. Methylene Chloride has been listed as a potential carcinogen by IARC and NTP. Methylene Chloride is not believed to pose a measureable risk to man when handled as recommended. Under some circumstances, mutagenic changes have been observed with Methyl Methacrylate in animal studies. Precautions should be taken to avoid unnecessary exposure to this cement.						
SHIPPING INFORMATION			SPECIAL HAZARD DESIGNATIONS			
DOT Shipping Name:	Flammable liquid, toxic, n.o.s. (Methyl acetate, Dichloromethane)		HMIS	NFPA	HAZARD RATING	
DOT Hazard Class:	3; Subsidiary Risk: 6.1		HEALTH:	3	2	0 - MINIMAL
Identification Number:	UN 1992		FLAMMABILITY:	3	3	1 - SLIGHT
Packaging Group:	II		REACTIVITY:	0	0	2 - MODERATE
Label Required:	Flammable Liquid & Toxic (Domestic & International)		PROTECTIVE			3 - SERIOUS
Exceptions:	None		EQUIPMENT:	B - H		4 - SEVERE
			B = Eye, Hand/Skin Protection (Normal use or application & small spill clean-up activities)			
			H = Eye, Hand/Skin and Respiratory Protection plus Impermeable Apron (When risk of immersion, dipping and/or splashing is present)			
SECTION III - PHYSICAL DATA						
APPEARANCE Clear, thin liquid	ODOR Ketone like odor		BOILING POINT (°F/°C) 104°F (40°C) Based on first boiling component: Methylene Chloride			
SPECIFIC GRAVITY @ 73°F ± 3.6° (23°C ± 2°) Typical 1.10 ± 0.040	VAPOR PRESSURE (mm Hg.) 355 mm Hg. @ 68°F (20°C) based on first boiling component, Methylene Chloride		PERCENT VOLATILE BY VOLUME (%) Approx. 80-95%			
VAPOR DENSITY (Air = 1) 2.93 based on Methylene Chloride	EVAPORATION RATE (BUAC = 1) Approx. 14.5 based on Methylene Chloride		SOLUBILITY IN WATER Solvent slightly miscible Resin precipitates			
VOC STATEMENT: Maximum VOC emissions as applied and tested per SCAQMD Rule 1168, Test Method 316A: 350 Grams/Liter (g/l). Meets VOC emission limits for Plastic Cement Welding.						
SECTION IV - FIRE AND EXPLOSION HAZARD DATA						
FLASH POINT 21°F (-6°C) T.C.C. based on MEK	FLAMMABLE LIMITS (Percent by Volume)			LEL	UEL	
				1.8	11.5	
FIRE EXTINGUISHING MEDIA Dry chemical, carbon dioxide or foam. Water may be an ineffective extinguishing agent.						
SPECIAL FIRE FIGHTING PROCEDURES The use of a SCBA is recommended for fire fighters. Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.						
UNUSUAL FIRE AND EXPLOSION HAZARDS Avoid hot surfaces and other sources of ignition.						

SECTION V - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY:	
_____ X _____ Inhalation	_____ X _____ Skin Contact _____ Eye Contact _____ Ingestion
EFFECT OF OVEREXPOSURE	
ACUTE:	
<u>Inhalation:</u>	Exposure to vapors may result in nausea, drowsiness, dizziness, headache, fatigue, other CNS effects and heart arrhythmias (irregular heart beats). Can cause irritation of eyes and nasal passages. Exposure to high concentrations may impair blood's ability to transport oxygen. Prolonged or repeated exposure to vapors may cause liver and kidney damage.
<u>Skin Contact:</u>	Repeated or prolonged contact may result in defatting of skin, irritation, contact dermatitis, rash, itching, swelling. May be absorbed through skin.
<u>Eye Contact:</u>	Direct exposure may result in irritation with corneal or conjunctival inflammation if not removed promptly. Vapors may irritate eyes.
<u>Ingestion:</u>	Moderately toxic. Irritant to digestive tract, may induce signs of central nervous system depression. Do not induce vomiting and obtain professional medical attention.
CHRONIC:	
<u>Inhalation</u>	‡ This material is an aspiration hazard and defats the skin. The ingredients are toxic by inhalation and ingestion and may be absorbed through the skin. Exposure by these routes may cause central nervous system depression, liver and kidney damage and may sensitize the heart muscle. Methylene Chloride may interfere with the oxygen carrying capacity of the blood. Methylene Chloride is a possible human cancer hazard based on test results with laboratory animals. Methylene Chloride has been listed as a potential carcinogen by IARC and NTP. Methylene Chloride is not believed to pose a measurable risk to man when handled as recommended. Under some circumstances, mutagenic changes have been observed with Methyl Methacrylate in animal studies. Precautions should be taken to avoid unnecessary exposure to this cement.
<u>Ingestion</u>	Ingestion of alcohol may increase the potential for development of toxic effects or reactions resulting from Methylene Chloride exposure.
REPRODUCTIVE EFFECTS	TERATOGENICITY MUTAGENICITY EMBRYOTOXICITY SENSITIZATION TO PRODUCT SYNERGISTIC PRODUCTS
N. AP.	POSS. N. AP. POSS. N. AP. N. AV.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: This material may aggravate an existing dermatitis. Individuals with pre-existing diseases of the heart, liver or kidney may have increased susceptibility to the toxicity of excessive exposures.	
EMERGENCY AND FIRST AID PROCEDURES	
<u>Inhalation:</u>	Remove patient to fresh air and if breathing stopped, give artificial respiration. If breathing is difficult, give oxygen. Contact physician immediately.
<u>Eye Contact:</u>	Immediately flush eyes with flowing water for 15 minutes and contact a physician.
<u>Skin Contact:</u>	Wash skin with soap and water. Remove contaminated clothing and shoes. Launder clothing before reuse. If irritation develops, get medical attention.
<u>Ingestion:</u>	Give 1 or 2 glasses of water or milk. Do not induce vomiting. Call physician or poison control center immediately.

SECTION VI - REACTIVITY

STABILITY	UNSTABLE		CONDITIONS TO AVOID:	Stable under normal conditions of storage and handling. Avoid contact or exposure to fire, heat, sparks, electric arcs, open flame and hot surfaces which can cause thermal decomposition.
	STABLE	X		
INCOMPATIBILITY (MATERIALS TO AVOID) Strong alkalis, oxygen, nitrogen, peroxide, potassium and reactive metals.				
HAZARDOUS DECOMPOSITION PRODUCTS This product gives out carbon monoxide (CO), carbon dioxide (CO ₂), Phosgene gas and smoke upon combustion or contact with reactive metals.				
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID	Keep away from heat, sparks, open flame and other sources of ignition.
	WILL NOT OCCUR	X		

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Evacuate area, ventilate and avoid breathing vapors. Dike area to contain spill. Clean up area (wear protective equipment) by mopping or with absorbent material and place in closed containers for disposal. Avoid contamination of ground and surface waters. Do not flush to sewer. If spill occurs indoors, turn off heating and/or air conditioning systems to prevent vapors from contaminating entire building.
WASTE DISPOSAL METHOD
Recovered liquids may be sent to a licensed reclaimer or incineration facility. Contaminated material must be disposed of in a permitted solid waste management facility. Follow local, State and Federal regulations. Material should not be allowed to drain into domestic sewer or storm drains. Consult disposal expert.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)	
Atmospheric levels should be maintained below established exposure limits contained in Section II. If airborne concentrations exceed those limits, use of a NIOSH approved positive-pressure, full-facepiece SCBA or positive-pressure, full-facepiece supplied air respirator (with an auxiliary positive pressure SCBA) is recommended. Even for emergency and other conditions where short term exposure guidelines may/may not be exceeded, use of an approved positive pressure self-contained breathing apparatus (SCBA) is recommended.	
VENTILATION	
Use only with adequate ventilation. Do not use in close quarters or confined spaces. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below 25 ppm TWA. Use only explosion-proof ventilation equipment. Monitoring should be performed to determine exposure level(s) IAW (in accordance with) 29 CFR 1910.1052.	
PROTECTIVE GLOVES	EYE PROTECTION
PVA coated or Latex-Nitrile rubber for dipping/immersion. Surgical gloves or solvent resistant barrier creme should provide adequate protection in normal adhesive bonding usage.	Splashproof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as appropriate for exposure.
OTHER PROTECTIVE EQUIPMENT AND HYGIENIC PRACTICES	
Impervious apron and a source of running water to flush or wash the eyes and skin in case of contact.	

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Store in a shaded place between 40°F - 110°F (5°C - 43.7°C). Keep away from all sources of heat, sparks, open flame and other sources of ignition. Close container after each use. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Train employees on all special handling procedures before they work with this product.
OTHER PRECAUTIONS
Follow all precautionary information given on container label, product bulletins and our solvent cementing literature. All material handling equipment should be electrically grounded.
The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.