

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION****Product identifier**

Trade name : PREMIUM CONVENTIONAL SAE 5W-30  
Motor Oil

**Details of the supplier of the safety data sheet**

Valvoline LLC  
100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)  
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

**Emergency telephone number**

1-800-VALVOLINE (1-800-825-8654)

**Regulatory Information Number**

1-800-TEAMVAL (1-800-832-6825)

**Product Information**

1-800-TEAMVAL (1-800-832-6825)

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=50.00 - < 60.00
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	>=30.00 - < 40.00

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=5.00 - < 10.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		Not a hazardous substance or mixture.	>=1.50 - < 5.00
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	>=1.50 - < 5.00

**SECTION 4. FIRST AID MEASURES**

General advice	: No hazards which require special first aid measures.
If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

Odour : No data available  
 Odour Threshold : No data available  
 pH : No data available  
 Melting point/freezing point : No data available  
 Boiling point/boiling range : No data available  
 Flash point : 394 - 480 °F / 201 - 249 °C  
 Method: Cleveland open cup  
 Evaporation rate : No data available  
 Flammability (solid, gas) : No data available  
 Self-ignition : No data available  
 Upper explosion limit / Upper flammability limit : 6 %(V)  
 Calculated Explosive Limit  
 Lower explosion limit / Lower flammability limit : 1 %(V)  
 Calculated Explosive Limit  
 Vapour pressure : 1.3333333 hPa (68 °F / 20 °C)  
 Calculated Vapor Pressure  
 Relative vapour density : No data available  
 Relative density : 0.876 (60.1 °F / 15.6 °C)  
 Density : 0.8599 g/cm3 (60.1 °F / 15.6 °C)  
 Solubility(ies)  
     Water solubility : No data available  
     Solubility in other solvents : No data available  
 Partition coefficient: n-octanol/water : No data available  
 Decomposition temperature :  
 No data available  
 Viscosity  
     Viscosity, dynamic : No data available

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

Viscosity, kinematic : 63 mm<sup>2</sup>/s (104 °F / 40 °C)

Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation

Skin contact

Eye Contact

Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): &gt; 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): &gt; 5 g/kg

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Acute oral toxicity : LD50 (Rat): &gt; 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): &gt; 5 g/kg

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): &gt; 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

**Components:**
**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Unlikely to cause eye irritation or injury.

**Components:**
**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Result : No eye irritation  
Assessment : No eye irritation

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Result : Slight, transient irritation  
Assessment : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : Slight, transient irritation  
Assessment : Slight, transient irritation

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Result : Slight, transient irritation  
Assessment : Slight, transient irritation

**Respiratory or skin sensitisation**
**Skin sensitisation**

Not classified based on available information.

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Components:**
**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**
**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

May be fatal if swallowed and enters airways.

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

May be fatal if swallowed and enters airways.



**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

**Further information**
**Product:**

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**
**Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment  
Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**Persistence and degradability****Components:**

No data available

**Bioaccumulative potential****Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-octanol/water : log Pow: Expected > 7

No data available

**Mobility in soil****Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

---

**SECTION 14. TRANSPORT INFORMATION**

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

**International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards**California Prop. 65**

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for carcinogenicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for reproductive/developmental toxicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

**The components of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

**SAFETY DATA SHEET**

Revision Date: 08/29/2019

Print Date: 12/19/2019

SDS Number: R0172013

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.9

VV177

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory

**TSCA list**


No substances are subject to TSCA 12(b) export notification requirements.

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION**
**Further information**

Revision Date: 08/29/2019

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p> 	<table border="1"> <tr> <td><b>HEALTH</b></td><td><b>0</b></td></tr> <tr> <td><b>FLAMMABILITY</b></td><td><b>1</b></td></tr> <tr> <td><b>PHYSICAL HAZARD</b></td><td><b>0</b></td></tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**


Combustible Liquid Class IIIB

**Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

	Page: 13
<b>SAFETY DATA SHEET</b>	Revision Date: 08/29/2019
	Print Date: 12/19/2019
	SDS Number: R0172013
PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil  VV177	Version: 1.9

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health

	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 08/29/2019
	Print Date: 12/19/2019
	SDS Number: R0172013
PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil  VV177	Version: 1.9

OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System