

MATERIAL SAFETY DATA SHEET



SECTION 1 - PRODUCT AND COMPANY INFORMATION

Refinish Products
19699 Progress Drive
Strongsville, OH 44149

EMERGENCY PHONE NUMBERS (412) 434-4515 (U.S.)
(24 hours/day):

(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)
0532-83889090 (China)

TECHNICAL INFORMATION: (440) 572-2800

PRODUCT SAFETY/MSDS INFORMATION: (412) 492-5555 7:00 a.m. - 4:30 p.m. EST

Product ID: DX586 (0808)
PRODUCT NAME: AIRCRAFT PAINT REMONER
SYNONYMS: None
ISSUE DATE: 05/02/2006
EDITION NO.: 3
CHEMICAL FAMILY: SOLVENT

EMERGENCY OVERVIEW:
CAUSES EYE IRRITATION. MAY CAUSE MODERATE SKIN IRRITATION. MAY BE ABSORBED THROUGH THE SKIN. VAPOR AND/OR SPRAY MIST HARMFUL IF INHALED. VAPOR IRRITATES EYES, NOSE, AND THROAT. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. This product is not expected to present any unusual hazards under fire or spill conditions. Read entire MSDS before use.

SECTION 2 - COMPOSITION INFORMATION

The following ingredient(s) marked with an "x" are considered hazardous under applicable U.S. OSHA and/or Canadian WHMIS regulations. If no ingredients are listed, then there are no U.S. OSHA and/or Canadian WHMIS hazardous ingredients in this product.

Material/ CAS Number	Percent	Hazardous
METHYLENE CHLORIDE 75-09-2	40 - 70	X
NAPHTHA 64742-48-9	15 - 40	X
METHYL ALCOHOL 67-56-1	1 - 5	X
PARAFFIN WAX 64742-51-4	0.5-1.5	X

SECTION 3 - HAZARDS IDENTIFICATION

ACUTE OVEREXPOSURE EFFECTS

EYE CONTACT:

Causes eye irritation. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact.

SKIN CONTACT:

May cause moderate skin irritation. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

SKIN ABSORPTION:

May be absorbed through the skin.

INHALATION:

Vapor and/or spray mist harmful if inhaled. Vapor irritates eyes, nose, and throat.

INGESTION:

May be fatal or cause blindness if swallowed.

SIGNS & SYMPTOMS OF OVEREXPOSURE:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

CHRONIC OVEREXPOSURE EFFECTS

Avoid long-term and repeated contact.

Repeated exposure to vapors above recommended exposure limits (see Section 8) may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Inhalation of high vapor concentrations of methylene chloride may cause kidney and liver damage, decrease the oxygen-carrying capacity of the blood, and has caused cancer in laboratory animals. No evidence exists that this material presents a cancer risk to humans.

The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact with this material to avoid any effects from repetitive acute exposures. See Section 11, of this MSDS for a detailed list of chronic health effects information available on individual ingredients in this product.

SECTION 4 - FIRST AID MEASURES

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.

EYE CONTACT:

Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

SKIN CONTACT:

Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

INHALATION:

Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information. If overexposure occurs, catecholamine drugs, such as epinephrine, should be used with special caution only in situations of emergency life support due to possible disturbances of cardiac rhythm.

INGESTION:

Gently wipe or rinse the inside of the mouth with water. Sips of water may be given if person is fully conscious. Never give anything by mouth to an unconscious or convulsing person. Do Not induce vomiting. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: Not Applicable.

FLASHPOINT TEST METHOD:

Pensky-Martens Closed Cup

UEL: Not Available.

LEL: Not Available.

AUTOIGNITION TEMPERATURE:

Not Available.

EXTINGUISHING MEDIA:

Use extinguishers appropriate for surrounding fire. Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

PROTECTION OF FIREFIGHTERS:

Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat. Halogenated hydrocarbon solvents can cause an explosion when used with aluminum components in a pressurized fluid system (pumps, heaters, valves, spray guns, tanks). Contact your supplier for advice on compatible pressurized fluid system components for use with formulations containing halogenated hydrocarbon solvents. May produce hazardous decomposition products when exposed to extreme heat. Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

SECTION 6 - ACCIDENTAL RELEASE MEASURE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:

Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

STORAGE:

Do not store above 120 degrees F. (48 degrees C.).

SECTION 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 8 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

PERSONAL PROTECTIVE EQUIPMENT

EYES:

Wear chemical-type splash goggles when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.

SKIN/GLOVES:

Wear protective clothing to prevent skin contact. Apron and gloves should be constructed of: impermeable material. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment. Clean contaminated clothing and shoes.

RESPIRATOR:

Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used. Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

GENERAL HYGIENE - ESTABLISHED EXPOSURE LIMITS

If Threshold Limit Values (TLVs) have been established by ACGIH, OSHA, Ontario or PPG, they will be listed below. These limits are intended for use in the practice of industrial hygiene as guidelines or recommendations in the control of potential workplace health hazards. These limits are not a relative index of toxicity and should not be used by anyone without industrial hygiene training.

Material/ CAS Number	Percent	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL
METHYLENE CHLORIDE 75-09-2	40 - 70	50 ppm	Not established	C- 1000 ppm	125 PPM
METHYL ALCOHOL 67-56-1	1 - 5	S- 200 ppm	250 ppm	S- 200 ppm	250 ppm
PARAFFIN WAX 64742-51-4	0.5-1.5	2 mg/m ³	Not established	2 mg/m ³	Not established

Material/ CAS Number	Percent	Ontario TWA	Ontario STEL	PPG IPEL	PPG STEL
METHYLENE CHLORIDE 75-09-2	40 - 70	50 ppm	Not established	Not established	Not established
METHYL ALCOHOL 67-56-1	1 - 5	S- 200 ppm	250 ppm	Not established	Not established

Key: ACGIH=American Conference of Governmental Industrial Hygienists; OSHA=Occupational Safety and Health Administration; TLV=Threshold Limit Value; TWA=Time Weighted Average; PEL=Permissible Exposure Limit; IPEL=Internal Permissible Exposure Limit; Ceiling=TLV or PEL Ceiling Limit; STEL=TLV or PEL Short-Term Exposure Limit; Skin= Skin Absorption Designation. [C- Ceiling Limit; S- Potential Skin Absorption; R-Respirable Dust]
Additional Information Not applicable.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES (FORMULA VALUES, NOT SALES SPECIFICATIONS)

SPECIFIC GRAVITY:	1.028
PHYSICAL STATE:	Liquid
Percent Solids:	2.46
Percent Volatile by Volume:	97.590
pH:	Not available.
ODOR THRESHOLD:	Not available.
Vapour Pressure:	47.7 mmHg
ODOR/APPEARANCE:	Non-viscous liquid with an odor characteristic of the ingredients listed in Section 2.
VAPOR DENSITY:	HEAVIER THAN AIR
Evaporation Rate:	1642
BOILING POINT OR RANGE:	86 - 351 Degrees F
Freezing Point or Range:	Not Applicable.
Melting Point or Range(°C):	Not Applicable.
Partition coefficient (n-octanol/water):	Not Applicable.
WEIGHT PER GALLON:	8.57 (U.S.) / 10.2 (IMPERIAL)

SECTION 10 - STABILITY AND REACTIVITY

STABILITY:

This product is normally stable and will not undergo hazardous reactions.

CONDITIONS TO AVOID:

None Known.

INCOMPATIBLE MATERIALS:

Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

HAZARDOUS POLYMERIZATION:

None Known.

HAZARDOUS DECOMPOSITION PRODUCTS:

- Carbon monoxide - Carbon dioxide

SECTION 11 - TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Material/ CAS Number	Percent	ORAL LD50 (g/kg)	DERMAL LD50 (g/kg)	INHALATION LC50 (mg/l)
METHYLENE CHLORIDE 75-09-2	40 - 70	2.14 g/kg	Not Available	Not Available
METHYL ALCOHOL 67-56-1	1 - 5	5.63 g/kg	15.80 g/kg	Not Available

CHRONIC TOXICITY**Ingredient Target Organ/Chronic Effects:**

- Causes blindness - Blood - Carcinogen - Kidney - Liver - Brain - Central nervous system - Lung

Mutagenicity Toxicity:

This has not been tested for this product.

Reproductive Toxicity:

This has not been tested for this product.

SUPPLEMENTAL HEALTH INFORMATION:

Material/ CAS Number	Percent	Ingredient Specific Animal Data:
METHYLENE CHLORIDE 75-09-2	40 - 70	Inhalation of high vapor concentrations of an ingredient(s) in this product may decrease the oxygen carrying capacity of the blood.
METHYL ALCOHOL 67-56-1	1 - 5	Cannot be made non-poisonous.

SECTION 12 - ECOLOGICAL INFORMATION

POTENTIAL ENVIRONMENTAL EFFECTS

Ecotoxicity: No Information Available.

ENVIRONMENTAL FATE

Mobility: No information available.

Biodegradation: No information available.

Bioaccumulation: No Information Available.

PHYSICAL/CHEMICAL

Hydrolysis: No information available.

Photolysis: No information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Provide maximum ventilation, only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Take up spilled material with sawdust, vermiculite, or other absorbent material and place in containers for disposal.

Waste material must be disposed of in accordance with federal, state, provincial and local environmental control regulations. Empty containers should be recycled by an appropriately licensed reconditioner/salvager or disposed of through a permitted waste management facility. Additional disposal information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Corrosive Liquid, Toxic, NOS
NOS Technical Name: Ammonium Hydroxide, Methylene Chloride
Hazard Class: 8
Subsidiary Class(es): 6.1
UN Number: UN2922
Packing Group: II

USA - RQ Hazardous Substances: Methylene Chloride, Ammonia

USA-RQ Hazardous Substance Methylene Chloride>1768.05

Threshold Ship Weight: Pounds, Ammonia>11493.1 Pounds

Marine Pollutant Name: None

USA Shipments Only - RQ Threshold Ship Weight: This is the total weight of this product that must be shipped to exceed the RQ quantity.

SECTION 15 - REGULATORY INFORMATION

INVENTORY STATUS

U.S. TSCA: This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA Inventory reporting requirements.

FEDERAL REGULATIONS**US Regulations**

Material/ CAS Number	Percent	CERCLA HS - RQ (LBS)	SARA EHS- TPQ (LBS)	SARA 313
METHYLENE CHLORIDE 75-09-2	40 - 70	1000 lbs	Not Listed	Listed
NAPHTHA 64742-48-9	15 - 40	Not Listed	Not Listed	Not Listed
METHYL ALCOHOL 67-56-1	1 - 5	5000 lbs	Not Listed	Listed
PARAFFIN WAX 64742-51-4	0.5-1.5	Not Listed	Not Listed	Not Listed

SARA 311/312

Health (acute): Yes

Health (chronic): Yes

Fire (flammable): Yes

Pressure: No

Reactivity: No

WHMIS HAZARD CLASS: - Class D, Division 2, Subdivision A

STATE/PROVINCIAL REGULATIONS

CALIFORNIA PROP. 65: WARNING: This product contains a chemical known to the State of California to cause cancer.

Additional Information

<u>Material/ CAS Number</u>	<u>Percent</u>	<u>IARC Group 1(Kno wn Human Carc.)</u>	<u>IARC Group 2A (Proba ble Carc.)</u>	<u>IARC 2B (Suspec ted Carc.)</u>	<u>ACGIH Carc.</u>	<u>NTP Known Carc.</u>	<u>OSHA Carc.</u>
METHYLENE CHLORIDE 75-09-2	40 - 70	N	N	Y	N	N	Y

Key: IARC- International Agency on the Research of Cancer; ACGIH- American Conference of Governmental Industrial Hygienists; NTP- National Toxicology Program *Denotes chemical as NTP Known Carcinogen; + Denotes NTP Possible Carcinogen; OSHA- Occupational Safety and Health Administration.

SECTION 16 - OTHER INFORMATION

Hazard Rating Systems

NFPA Rating: 2 30

HMIS Rating: 2*30

Rating System: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Effects.

HMIS=Hazardous Materials Identification System; NFPA=National Fire Protection Association;

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.

PREPARED BY: Product Safety Department

REASON FOR REVISION: Section 15 has been updated. Section 1 has been updated. Section 4 has been updated. Section 8 has been updated. Section 14 has been updated. Date. Edition.

Updated MSDS
format.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200), the supplier notification requirements of SARA Title III, Section 313 and other applicable right-to-know regulations.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

DX586 000001 (00229060.003)(11/11/04)
990105, 000, 0808

*** END OF MSDS ***