

100 Mansell Court East, Suite 300; Roswell, GA 30076 Telephone (770) 594-0660 Fax: (770) 645-3460

Customer Service: (800) 485-2529

MATERIAL SAFETY DATA SHEET

Section 1 - Material Identity

Product Trade

EPK

Name(s):

Common Names(s): Kaolin Clay, China Clay

Chemical Name:

Al,Si,O,(OH)

CAS Number: Physical Form: 1332-58-7 (In TSCA Inventory)

Light gray to white powder

HMIS Ratings

Health Hazard	1
Flammability Hazard	0
Reactivity Hazard	0
Max. Personal Protection	Ε

Manufacturer's Name & Address:

The Feldspar Corporation, 100 Mansell Court East,

Suite 300; Roswell, GA 30076

Emergency Telephone:

(800) 424-9300 CHEMTREC

Section 2 - Ingredients and Hazards

<u>Ingredient</u>	Wt. % (Approx.)	CAS No.	OSHA PEL*	ACGIH TLV*
Kaolinite	> ~95%	1332-58-7	5 mg/m³ Resp. 15 mg/m³ Total	2 mg/m³Resp.
Crystalline Silica, Quartz	~0.1% - 4.0%	14808-60-7	0.1 mg/m ³ Resp.	0.025 mg/m³ Resp.
Water	< 2%			

^{*} Unless otherwise noted, all PEL and TLV values are reported as 8 hour time weighted averages

Section 3 - Hazards Identification and Cautions

Appearance: Light gray to white powder

Primary Routes of Entry: Skin contact, skin absorption, eye contact, ingestion: Hazard Classification - None. (Historical basis for classification.)

Target Organs: Eye, skin and lungs

Medical Conditions Aggravated by Exposure: Skin contact may aggravate existing dermatitis. Breathing excessive quantities of kaolin dust may aggravate pre-existing respiratory conditions.

Potential Health Effects:

Eye Contact: This product may produce irritation upon contact with the eye. See also Section 4 below.

Skin Contact: Prolonged or repeated exposure may cause skin irritation. Kaolin is not expected to be absorbed through the skin in harmful amounts or to produce an allergic skin reaction. See also Section 4 below.

Ingestion: No adverse effect is expected. If ingested, seek medical advice. See also Section 4 below.

Inhalation: Inhalation of excessive quantities of kaolin dust may irritate the respiratory tract. See also Section 4 below. Prolonged exposure to respirable kaolin dust without the use of appropriate respiratory equipment could adversely affect respiratory function including fibrogenic response. See Am. Rev. Respir. Dis. 1983; 127:215-220; 231-253; 141-142; Doc. Thres. Limit Values and Bio. Exp. Ind., Sixth Edition, 1991: OSHA PEL-29 C.F.R. 1910.1000,

Sub chronic, Chronic: None expected. No applicable information was found concerning any potential health effects resulting from sub chronic or chronic exposure to kaolin.

This product typically contains crystalline silica (quartz sand) above 0.1% as a naturally occurring impurity. The International Agency for Research on Cancer has concluded that "crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic

to humans (Group I)."It also noted that carcinogenicity was not detected in all industrial circumstance studies, and may be dependent on external factors affecting its biological activity or distribution of its polymorphs. (See IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68 (1997).) Exposure to respirable silica has also been associated with silicosis, scieroderma, and nephrotoxicity. (See Occupational Lung Disorders, Third Edition, Chapter 12 (1994) and American Journal of Respiratory and Critical Care Medicine, Volume 155, pp 761-765 (1997).)

Section 4 - First Aid Measures

Eye Contact:	Follow good industrial hygiene practices. In case of contact, immediately flush eyes with plenty of water. Seek medical aid necessary.
Skin Contact:	Follow good industrial hygiene practices. Wash affected skin areas thoroughly with soap and water. Seek edical aid if necessary.
Inhalation:	Follow good industrial hygiene practices. If excessive exposure by inhalation is suspected, remove to fresh air. If necessary, MSHA/NIOSH or OSHA/NIOSH approved respirator is recommended. Seek medical aid if necessary.
Ingestion:	Follow good industrial hygiene practices. If ingested, do not induce vomiting. If conscious, drink two glasses of water. See medical aid if necessary.

Section 5 - Fire Fighting Measures

Explosion Data: Not Explosive

Not Applicable

Not Applicable UEL: Extinguishing Media: Product will not burn.

LEL:

NFPA 704M Hazard Classification:

Health: 1

Flammable: 0

Reactivity: 0

Flash Point: Not Applicable

Auto-Ignition: Not Applicable

Flammability: Not Flammable or Combustible

Use appropriate extinguishing media for packaging material if applicable.

Section 6 - Accidental Release Measures

Vacuum, pump or scoop spilled material into containers for reclaiming or disposal. Use proper respiratory and personal protective equipment. MSHA/NIOSH or OSHA/NIOSH approved respirator recommended. Spilled materials may cause slippery conditions when wet. Care should be exercised when walking on spills on floors or concrete pads. No neutralizing chemicals required. Material is inert and nonreactive. Kaolin is not a CERCLA listed hazardous substance.

Section 7 - Handling and Storage

Storage in a cool, dry location is recommended...

Spilled materials may cause slippery conditions when wet. Care should be exercised when walking on spills on floors or concrete pads.

Minimize dust generation & accumulation.

If excessive dust is generated, provide adequate ventilation and use proper respiratory and personal protective equipment. MSHA/NIOSH or OSHA/NIOSH approved respirator recommended.

Section 8 - Exposure Control/Personal Protection

Hazardous Ingredient	Weight %(Approx.)	CAS No.	MSHA PEL	OSHA PEL	ACGIH TLV
Kaolinite		1332-58-7	10 mg/m3 Total	15 mg/m3 Total	2 mg/m³ Resp.
				5 mg/m3 Resp.	
Crystalline Silica, Quartz	~0.1% - 4.0%	14808-60-7	0.1 mg/m3 Resp.	0.1 mg/m³ Resp.	0.025 mg/m³ Resp.

Unless otherwise noted, all PEL and TLV values are reported as 8 hour time weighted averages (TWA).

Respiratory Protection:

If respirator is required, use of a MSHA/NIOSH or OSHA/NIOSH approved respirator is recommended.

Ventilation:

Use exhaust ventilation, if required, to maintain dust concentration below recommended exposure limits.

Protective Equipment: Wear side shield safety glasses. Rubber gloves are recommended for prolonged exposure.

Section 9 - Physical and Chemical Properties

Physical State:	Solid	Boiling Point:	Not Applicable
Appearance & Odor:	Light gray to white powder. Earthy odor	Freezing Point:	Not Applicable

	when wet	•	
pH (Aqueous Suspension):	4.0 - 6.0	Vapor Pressure:	Not Applicable
Specific Gravity:	~2.6	Vapor Density:	Not Applicable
% Solubility in Water:	Insoluble	VOC:	None
Melting Point:	Not Determined > 1500 °C	Evaporation Rate:	Not Applicable

	Not Determined > 1500 C	Evaporation Nate.	rvor Appricable
	Section 10 Stability and	Danatatan i sa isali	
	Section 10 - Stability and	Reactivity	
Chemically Stable? Yes X	No		
	es? Yes X No (See below)	litions. When arreaded to high tous	wanaturaa fraa awarta aan
	oducts: Ball clay is stable under normal cond		
	dymite (above 870°C) or cristobalite (above 1-	470 C) which have higher health h	azards than quartz.
(Tridymite and cristobalite (TWA-	rdous Polymerization: None, inert and nonro		
Incompatibility (Materials to Ave		eactive.	
meompatibility (materials to Av	Section 11 - Disposal Con	didaya tin barra sa	
PA Woote Numbers Vinder DCD A			1 '11 U.1
tate and federal requirements.	(40 CFR 261) kaolin is a non-hazardous was	te. Dispose of waste material in ac	cordance with all local,
	Section 12 - Toxicological	Information	
Kaolin - CAS No. 1332-58-7			
Primary Route of Exposure: X	Skin; X Eye Contact; X Inhalation; X	_ Ingestion	
Kaolin - Acute Health Hazards:			
Eye contact may cause mechanical	irritation.		
Skin contact may aggravate existin	g dermatitis		
	tinuous exposure to excessive quantities of du	ist may aggravate existing asthmat	ic or respiratory conditions.
No adverse effect expected when in	ngested.		
Kaolin - Chronic Health Hazards	*:		
Carcinogenicity*: NTP? No	IARC*? No	OSHA*? No	
•			
Mutagenicity: None known	Teratogenicity: None known	Reproductive Ef	fects: None known
See Section 3 for discuss	ion of amentalling cities		
See Section 3 for discuss			0 (
	Section 13 - Transport In	formation	
	t Regulated		:
OOT Classification: Not Regulated nternal UN:	I DOT/IMO Classification: Not Regulated	iated	
aternat ett. 190	t Negarated		

Section 14 - Regulatory Information

FDA: Kaolin is generally recognized as safe (GRAS) under the FDA in accordance with 21 CFR 186.1256. Additionally kaolin is established as a component of the uncoated or coated food contact surface of paper and paperboard in accordance with 21 CFR 176.170 (aqueous and fatty foods) and CFR 176.180 (dry foods).

SARA Title III Section 302 Extremely Hazardous Substances: This product does not contain extremely hazardous substances subject to the reporting requirements of Section 302 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 355. SARA Title III Section 311 and 312 Health and Physical Hazard Categories per 40 CFR 370.2;

[<u>Immediate</u>	<u>Delayed</u>	Fire	Pressure	Reactivity
-	Yes	Yes	No		No

SARA Section 313 Notification: This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TSCA: Product is listed in Initial Inventory, Vol. 1, Appendix A, CAS No. 1332-58-7.

The International Agency for Research on Cancer has concluded that "crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group I)." It also noted that carcinogenicity was not detected in all industrial circumstance studies, and may be dependent on external factors affecting its biological activity or distribution of its polymorphs. (See IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 68 (1997).) Exposure to respirable silica has also been associated with silicosis, seleroderma, and nephrotoxicity. (See Occupational Lung Disorders, Third Edition, Chapter 12 (1994) and American Journal of Respiratory and Critical Care Medicine, Volume 155, pp 761-765 (1997).)

WARNING: This product may also contain extremely small amounts of one or more naturally-occurring materials known to the State of California to cause cancer, birth defects, or other reproductive harm.

While this information and recommendations set forth herein are believed to be accurate as of the date hereof, IMERYS NORTH AMERICA CERAMICS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

MERYS is a business name that includes Imerys North America Ceramics of which The Feldspar Corporation is a member. Registered in the USA. Registered Office: 100 Mansell Court East, Suite 300, Roswell, GA 30076.

Date Prepared: <u>04/03/2006</u> Revised: <u>08/13/2008</u>