



SAFETY DATA SHEET

Issuing Date 28-Oct-2016

Revision Date 28-Oct-2016

Revision Number 0

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name SCRUBS® Graffiti & Paint Remover Towels

Other means of identification

Product Code(s) 90101, 90130

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Graffiti Remover

Uses advised against None reasonably foreseeable

Supplier's details

Initial Supplier
ITW Permatex Canada
1-35 Brownridge Road
Halton Hills, ON, L7G 0C6
Canada

Supplier Address
ITW PRO BRANDS
805 E. Old 56 Highway
Olathe, KS 66061
TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone Number 800-535-5053 Infotrac

2. HAZARDS IDENTIFICATION

Classification

This product is considered hazardous according to the criteria set within the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

Serious Eye Damage/Eye Irritation	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable liquids	Category 2

Label Elements

Danger**Hazard Statements**

Causes serious eye irritation
May cause drowsiness or dizziness
Highly flammable liquid and vapor.

Physical and Health Hazards Not Otherwise Classified

Not applicable.

Precautionary Statements**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Keep cool.

General Advice

- None

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Call a POISON CENTER or doctor/physician if you feel unwell.

Fire

- In case of fire: Use CO₂, dry chemical, or foam for extinction.

Storage

- Store in a well-ventilated place. Keep container tightly closed.
- Store locked up.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Other information

Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Dimethyl adipate	627-93-0	20.63	-	-
Dimethyl glutarate	1119-40-0	20.59	-	-
Tripropylene glycol monomethyl ether	25498-49-1	14.85	-	-
Propylene glycol monomethyl ether	107-98-2	11.4	-	-
Acetone	67-64-1	9	-	-
2-Butoxyethanol	111-76-2	7.4	-	-
n-Amyl acetate	628-63-7	3.8	-	-
Dimethyl succinate	106-65-0	1.63	-	-

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
Ingestion	Not an expected route of exposure. If swallowed: Call a physician or Poison Control Center immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.
Protection of First-aiders	Remove all sources of ignition. Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Eye irritation/reactions. Drowsiness. Dizziness.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). Dry chemical. Water fog. Foam. Fire may float as if an oil fire.

Unsuitable Extinguishing Media None

Specific Hazards Arising from the Chemical Flammable. Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Hazardous Combustion Products Soot. Smoke, Fume, Incomplete combustion products, Oxides of carbon.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters Use water spray to cool surrounding containers. Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area) Take precautionary measures against static discharges. Pay attention to flashback. Avoid contact with the skin and the eyes. Use personal protective equipment as required. Do not breathe vapors or spray mist. Ensure adequate ventilation.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Non-sparking tools should be used. Small spillage: Wipe up with absorbent material (e.g. cloth, fleece). Large spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Do not smoke. Use only with adequate ventilation. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition. Use only in an area containing flame proof equipment. Do not breathe vapors or spray mist.

Conditions for safe storage, including any incompatibilities

Storage Store in cool/well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from heat and sources of ignition. Do not contaminate food or feed stuffs.

Incompatible Products Strong alkalis. Acids. Oxidizing agents. Alkali metal hydroxides.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propylene glycol monomethyl ether 107-98-2	STEL: 100 ppm TWA: 50 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m ³	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³

2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
n-Amyl acetate 628-63-7	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 525 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 525 mg/m ³

Appropriate engineering controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Risk of contact, wear: Goggles.
Skin and Body Protection Risk of contact: Antistatic boots. Wear fire/flamm resistant/retardant clothing. Impervious gloves.

Respiratory Protection None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use. Provide regular cleaning of equipment, work area and clothing. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State Liquid.
Odor None. **Appearance** Colorless.
Odor Threshold No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	6.3	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	100 °C / 212 °F	None known
Flash Point	16.67 °C / 62 °F	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	> 1	None known
Specific Gravity	0.986	None known
Water Solubility	Miscible with water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Highly flammable liquid and vapor.

Explosive Properties No data available
Oxidizing Properties No data available

Other information

VOC Content (%) 30

10. STABILITY AND REACTIVITY

Reactivity	No data available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Incompatible products. Heat, flames and sparks.
Incompatible materials	Strong alkalis. Acids. Oxidizing agents. Alkali metal hydroxides.
Hazardous decomposition products	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	May cause drowsiness and dizziness.
Eye Contact	Causes serious eye irritation. May cause eye irritation including redness, tearing, itching, and swollen eyes.
Skin Contact	Causes mild skin irritation
Ingestion	Not an expected route of exposure. May be harmful if swallowed.

Numerical measures of toxicity - Product

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral	2187 mg/kg; Acute toxicity estimate
LD50 Dermal	11674 mg/kg; Acute toxicity estimate
Inhalation	
dust/mist	9.9 mg/L; Acute toxicity estimate
Vapor	149 mg/L; Acute toxicity estimate

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Dimethyl adipate	= 1920 mg/kg (Rat)	-	-
Dimethyl glutarate	= 8191 mg/kg (Rat)	-	> 5.6 mg/L (Rat) 4 h
Tripropylene glycol monomethyl ether	= 3200 mg/kg (Rat)	= 15440 mg/kg (Rabbit)	-
Propylene glycol monomethyl ether	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat) 6 h
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
2-Butoxyethanol	= 470 mg/kg (Rat)	= 400 mg/kg (Rabbit) = 2270 mg/kg (Rat)	= 450 ppm (Rat) 4 h
n-Amyl acetate	> 1600 mg/kg (Rat)	-	-
Dimethyl succinate	> 5 g/kg (Rat)	> 5 g/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Eye damage/irritation	Irritating to eyes.
Respiratory or Skin Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Carcinogenicity	Contains no ingredients above reportable quantities listed as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
---------------	-------	------	-----	------

2-Butoxyethanol	A3	Group 3	
-----------------	----	---------	--

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

Reproductive Toxicity	No information available.
STOT - single exposure	May cause drowsiness and dizziness
STOT - repeated exposure	No information available.
Aspiration Hazard	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Dimethyl glutarate 1119-40-0		LC50 96 h: 19.6 - 26.2 mg/L static (Pimephales promelas)		EC50 48 h: 122.1 - 163.5 mg/L (Daphnia magna)
Tripropylene glycol monomethyl ether 25498-49-1		LC50 96 h: = 11619 mg/L static (Pimephales promelas)		EC50 48 h: > 10 mg/L (Daphnia magna)
Propylene glycol monomethyl ether 107-98-2		LC50 96 h: 4600 - 10000 mg/L static (Leuciscus idus) LC50 96 h: = 20.8 g/L static (Pimephales promelas)		EC50 48 h: = 23300 mg/L (Daphnia magna)
Acetone 67-64-1		LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
2-Butoxyethanol 111-76-2		LC50 96 h: = 1490 mg/L static (Lepomis macrochirus) LC50 96 h: = 2950 mg/L (Lepomis macrochirus)		EC50 24 h: 1698 - 1940 mg/L (Daphnia magna) EC50 48 h: > 1000 mg/L (Daphnia magna)
n-Amyl acetate 628-63-7		LC50 96 h: = 650 mg/L static (Lepomis macrochirus)		
Dimethyl succinate 106-65-0		LC50 96 h: 50 - 100 mg/L static (Brachydanio rerio)		

Persistence and Degradability No information available.**Bioaccumulation** No information available.

Chemical Name	Log Pow
Propylene glycol monomethyl ether	-0.437
Acetone	-0.24
2-Butoxyethanol	0.81
Dimethyl succinate	0.19

Mobility No information available.**Other Adverse Effects** No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Should not be released into the environment. Dispose of in accordance with local/regional/national regulations.

Contaminated Packaging Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone - 67-64-1		Included in waste stream: F039		U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable
n-Amyl acetate	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper shipping name Consumer commodity
Hazard Class ORM-D
Description Consumer commodity, ORM-D
Emergency Response Guide Number 128

TDG

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
Description UN1263, Paint, 3, II

MEX

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
Description UN1263, Paint, 3, II

IATA

UN-Number UN1263
Proper Shipping Name Paint related material
Hazard Class 3
Packing Group II
ERG Code 3L
Description UN1263, Paint related material, 3, II

IMDG/IMO

UN-Number UN1263
Proper Shipping Name Paint
Hazard Class 3
Packing Group II
EmS No. F-E, S-E
Description UN1263, Paint, 3, II, (16.67°C c.c.)

15. REGULATORY INFORMATION

International Regulations

Ozone depleting substances Not applicable
Persistent Organic Pollutants Not applicable

Hazardous Waste

Chemical Name	Basel Convention (Hazardous Wastes)
Acetone	Y42

The Rotterdam Convention (Prior Informed Consent) Not applicable

International Convention for the Prevention of Pollution from Ships (MARPOL) Not applicable

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.
IECSC -

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Tripropylene glycol monomethyl ether	25498-49-1	10-30	1.0
2-Butoxyethanol	111-76-2	5-10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Amyl acetate	5000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Amyl acetate	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Tripropylene glycol monomethyl ether	X		X	X	
Propylene glycol monomethyl ether	X	X	X	X	X
Acetone	X	X	X		X
2-Butoxyethanol	X	X	X	X	X
n-Amyl acetate	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 3 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazard 2 Flammability 3 Physical Hazard 0 Personal Protection X

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 28-Oct-2016
Revision Date 28-Oct-2016
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet